
CL828-xx Aero cleat Instructions


Compact cleats that are rigged on a rope. Nylon and alloy versions.
Easy to rig and adjust. Strong and wear resistant.
Ideal for forestay tensioning, kitesurfing, sports netting, sun sails, canvas structures, tie-downs, radio masts and aerials.

Standard rigging for all cleats
2:1 advantage






3 - 4mm
(⅛" – 5⁄32") Ø




Move cleat along the rope by hand. No tools required.

When using 3mm rope, take an extra turn round centre pillar.




CL828-63 (CL828 Aero base with black nylon CL263) 15gm. 0.5oz.

CL828-68 (CL828 Aero base with alloy CL268 silver)
CL828-68AN (CL828 Aero base with alloy CL268 hard anodised) 21gm. 0.75oz.



Rig like this to make a loop.




Rigs with
2:1 advantage




Rigging like this = no rope tail.

CL828-70 (CL828 Aero base with alloy CL270 silver)
CL828-70AN (CL828 Aero base with alloy CL270 hard anodised) 24gm. 0.8oz.




CL828-70 Rigged with 4:1advantage for running rigging

4:1advantage




CL828-70 Rigged with 4:1advantage for standing rigging

CL828-77 (CL828 Aero base with alloy CL277 silver)
CL828-77AN (CL828 Aero base with alloy CL277 hard anodised) 23gm. 0.85oz.



Rigging like this = no rope tail.

CL828-77 Rigged with 2:1advantage



Rig like this to make a loop.

© Clamcleats Ltd